

# NPI Profilleri



Kısa İşaret NPI	Ağırlık G kg/m	Boyutlar						Kesit Alanı F cm <sup>2</sup>	Toplam Yüzey Alanı S m <sup>2</sup> /m	2) Eğme Eksenleri İçin						3) S <sub>x</sub> cm	4) S <sub>x</sub> cm		
		h tolerans	b tolerans	s tolerans	t tolerans	r1	r2			I <sub>x</sub> cm	x-x W <sub>x</sub> cm	I <sub>x</sub> cm <sup>4</sup>	I <sub>y</sub> cm	Y-Y W <sub>y</sub> cm	I <sub>y</sub> cm <sup>4</sup>				
80	5.94	80	42	±1.5	3.9	5.9	-0.5	3.9	2.3	7.57	0.304	77.8	19.5	3.20	6.29	3.00	0.91	11.4	6.84
100	8.34	100						50	4.5	6.8	4.5	2.7	10.6	0.370	171	34.2	4.01	12.2	4.88
120	11.1	120	58	5.1	7.7	5.1	3.1	14.2	0.439	328	45.7	4.81	21.5	7.41	1.23	31.8	10.3		
140	14.3	140	66	5.7	8.6	5.7	3.4	18.2	0.502	573	81.9	5.61	35.2	10.7	1.40	47.7	12.0		
160	17.9	160	74	6.3	9.5	6.3	3.8	22.8	0.575	935	117	6.40	54.7	14.8	1.55	68.0	13.7		
180	21.9	180	82	6.9	10.4	6.9	4.1	27.9	0.640	1450	161	7.20	81.3	19.8	1.71	93.4	15.5		
200	26.2	200	90	7.5	11.3	7.5	4.5	33.4	0.709	2140	214	8.00	117	26.0	1.87	125	17.2		
220	31.1	220	98	8.1	12.2	8.1	4.9	39.5	0.775	3060	278	8.80	162	33.1	2.02	162	18.9		
240	36.2	240	106	8.7	13.1	8.7	5.2	46.1	0.844	4250	354	9.59	221	41.7	2.20	206	20.6		
260	41.9	260	113	9.4	14.1	9.4	5.6	53.3	0.906	5740	442	10.4	288	51.0	2.32	257	22.3		
280	47.9	280	119	10.1	15.2	10.1	6.1	61.0	0.966	7590	542	11.1	364	61.2	2.45	316	24.0		
300	54.2	300	125	10.8	16.2	10.8	6.5	69.0	1.03	9800	653	11.9	451	72.2	2.56	381	25.7		
320	61.0	320	131	11.5	17.3	11.5	6.9	77.7	1.09	12510	782	12.7	555	84.7	2.67	457	27.4		
340	68.0	340	137	12.2	18.3	12.2	7.3	86.7	1.15	15700	923	13.5	674	98.4	2.80	540	29.1		
360	76.1	360	143	13.0	19.5	13.0	7.8	97.0	1.21	19610	1090	14.2	818	114	2.90	638	30.7		
380	84.0	380	149	13.7	20.5	13.7	8.2	107	1.27	24010	1260	15.0	975	131	3.02	741	32.4		
400	92.4	400	155	14.4	21.6	14.4	8.6	118	1.33	29210	1460	15.7	1160	149	3.13	857	34.1		
425	104	425	163	15.3	23.0	15.3	9.2	132	1.41	36970	1740	16.7	1440	176	3.30	1020	36.2		
450	115	450	170	16.2	24.3	16.2	9.7	147	1.48	45850	2040	17.7	1730	203	3.43	1200	38.3		
475	128	475	178	17.1	25.6	17.1	10.3	163	1.55	56480	2380	18.6	2090	235	3.60	1400	40.4		
500	141	500	185	18.0	27.0	18.0	10.8	179	1.63	68740	2750	19.6	2480	268	3.72	1620	42.4		
550	166	550	200	19.0	30.0	19.0	11.9	212	1.80	99180	3610	21.6	3490	349	4.02	2120	46.8		
600	199	600	215	21.6	32.4	21.6	13.0	254	1.92	139000	4630	23.4	4670	434	4.30	2730	50.9		

